

CLP422

4G Industry Router



Product advantages

- ❖ Supports standard MINI PCIE interface
- ❖ Optional 4G wireless communication module with qualcomm MDM9X07 platform or ASR platform
- ❖ Support dual network ports
- ❖ Support dual WIFI antenna
- ❖ Support extended GPIO
- ❖ Stable performance and high cost performance
- ❖ Wide application scenarios

CLP422

4G Industry Router

Available modules	MDM9X07 series: CLM920_NC5/CLM920_TE5/CLM920_TB5/CLM920_TD5 ASR series: CLM920_AC5	
WIFI chip platform	MTK 7620A	
Size	118 × 115 × 27 mm	
BA ND	Adaptation CLM920_NC5	LTE B1/B3/B5/B8/B38/B39/B40/B41
		UMTS/HSDPA/HSPA+ B1/B3/B5/B8
		CDMA 1X/EVDO BC0
		GSM/GPRS/EDGE 850/900/1800
	Adaptation CLM920_TB5	LTE B1/B3/B5/B8/B38/B39/B40/B41
		UMTS/HSDPA/HSPA+ B1/B3/B5/B8
		GSM/GPRS/EDGE 850/900/1800
	Adaptation CLM920_TE5	LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41
		UMTS/HSDPA/HSPA+ B1/B3/B5/B8
		GSM/GPRS/EDGE 850/900/1800
	Adaptation CLM920_TD5	LTE B1/B2/B3/B4/B5/B7/B8/B17/B20/B28/B38/B39/B40/B41
		WCDMA B1/B2/B5/B8
		CDMA 1X/EVDO BC0
		GSM/GPRS/EDGE 850/900/1800/1900
	Adaptation CLM920_AC5	LTE B1/B3/B5/B8/B38/B39/B40/B41
		WCDMA B1/B5/B8
LTE rate	FDD-LTE 150M DL / 50M UL Cat4	
	TDD-LTE 130M DL / 35M UL Cat4	
SIM card	Support Micro SIM card	
Serial port	Support one debug serial port and one standard RS232 serial port	
RJ45 Network port	Support dual network ports	
GPS	Required module supports GPS	
RESET	Support reset button	
Power Interface Model	Molex 436500200	
Debug serial port spacing	2.54mm	
LED Indicator light	LINK0/LINK1/WIFI Indicator light/Power light/PPP light/4G network indicator	
Dial method	RNDIA/GobiNet	
Operating system	Windows series: WIN CE / Linux; Android 4.0-6.0	
Operating temperature	-20℃ - 80℃	
Operating Voltage	5-35V	
WebUI	Address 192.168.1.1, login account admin: admin	